

TouchPro 3

TECHNICAL DATA

The TouchPro 3 for the NetSeries system is designed to operate in challenging industrial environments. Its excellent environmental adaptability, IP65-rated front panel and high voltage and temperature design enables it to operate in a wide range of environmental conditions. The fanless design allows it to run 24/7 without affecting service life or reliability.

CPU	N5100 processor	Bluetooth	BT4.2 (BLE)
Operating system	Optional: Windows 11 Home Windows 11 Pro	WAN (optional)	2G/3G/4G
Memory	RAM: 8GB ROM: 128GB M.2 interface SATA III signal	I/O interface	(1) Standard SIM card Standard USB-A (2) USB3.0 USB2.0 (1) DC 12V power connector (1) ϕ 3.5mm standard earphone jack (2) RJ45, 10M/100M/1000M adaptive (1) HDMI 2.0a mini Optional: Extensive slot SATA/Phoenix terminal/TPM
Display	Type: LCD Size: 10.1 inch 16:10 Resolution: 800x1280 Brightness: 700cd/m2	Certification	Front panel IP65
Touch panel	10 PCAP, G+G	Environment	Working temperature: -4°F to 120°C Storage temperature: -22°F to 158°F Operating humidity: 95% non-condensing
Dimension	approx. 10x6x2 inches	Adapter	Input: 100-240V AC 50/60Hz Output: 12VDC4.0A
Weight	approx. 2.5 pounds		
Buttons	1 power (with indicator)		
Speaker	Optional: Built-in 4 Ω /2W, one for two		
WIFI	WiFi chip intel 9461 Frequency band: WiFi 802.11 (a/b/g/n/ac) 2.4G+5.8G dual frequency WiFi		

